



Integrity in our product, our workmanship, our environment

18 Whitbread Street Taree NSW 2430

t: (+61) 0265515022 f: 0265515023

e: contact@loganleigh.com.au w: www.loganleigh.com.au

LOGAN LEIGH BAMBOO BENCH TOPS

TECHNICAL INFORMATION AND FIXING INSTRUCTIONS

WE OFFER THIS INFORMATION WITH A DESIRE TO HELP YOU ENSURE THAT YOUR BAMBOO PRODUCT IS A LASTING ONE. LOGAN LEIGH CANNOT ACCEPT ANY RESPONSIBILITY IN THE ABSENCE OF THIS INFORMATION BEING ADHERED TO.

Logan Leigh offers you a 5 year guarantee against structural breakdown in all bamboo bench tops, providing the conditions relating to handling and storage are adhered to, and that the product is not used in areas of extreme climatic conditions. It is essential that installation procedures are strictly adhered to, or warranty may be void. This product is fabricated for interior use only.

PLEASE NOTE: Logan Leigh's Warranty will NOT apply to any work performed on the benchtops by anyone other than Logan Leigh. E.g. Alterations / trimming / sealing or cut-outs etc.

Do not allow the slabs to become heated or damp at any stage

This includes transport, storage and or during fabrication. Direct sunlight and drying breezes on unsealed slabs (especially end-grain) can have a damaging effect. Slabs should be stored on gluts/supports to allow air to circulate. It is recommended a plastic cover be placed on the bare sanded slab in between the fabrication processes (prior to sealing), especially if this takes place over a few days.

Filling of Imperfections

The recommended product for the filling of cracks or gaps if necessary is Timber Mate "Hardwood colour" water based wood filler available from Bunnings and selected paint stores. Ensure the manufacturer's instructions are followed.

Cut-outs

Sink and hot-plate cut-outs must be fully sealed with at least **THREE COATS** of polyurethane, applied with a brush. Cut-outs should be located no closer than 100mm from the end of the benchtop. DO NOT use silicon products to seal cut-outs.

Sealing or polishing

All surfaces including top, underside, edges and all cut-outs, **MUST** be sealed with at least three coats of two pack polyurethane to prevent moisture loss/gain. If using oil or other bench top surface finishes we strongly **recommend** that cut outs be sealed with three coats of polyurethane applied with a brush. If the polyurethane coating is removed while trimming or fitting the top, it must be resealed with three coats of brushed-on polyurethane. All sealing should be done as soon as possible after cutting or trimming.

Fixing to Sub-Frame

To allow the bench top a small amount of natural movement, any oversize or elongated holes should be bored through the back section of sub-frame. A minimum number of screws and washers can then be used to fasten down the bench top.

Manufacturing suppliers to the kitchen &
joinery industry



Integrity in our product, our workmanship, our environment

18 Whitbread Street Taree NSW 2430

t: (+61) 0265515022 f: 0265515023

e: contact@loganleigh.com.au w: www.loganleigh.com.au

Heat Protection

Protection between the benchtop and hot appliances is necessary. Adequate ventilation and insulation is suggested, especially for under bench lighting, refrigerator motors, dishwashers etc. which create heat build-up.

To maintain your Polyurethane Surface

Wipe over with a damp cloth or occasionally a small amount of detergent. Never use wax or silicone furniture polish as future recoating of the bench tops will be made difficult.

PLEASE NOTE: THIS PRODUCT IS NOT SUITABLE FOR EXTERIOR USE

For further Technical information, please contact LOGAN LEIGH

t: (02) 6551 5022 or fax: (02) 6551 5023 e: contact@loganleigh.com.au



**Manufacturing suppliers to the kitchen &
joinery industry**